

**Touch  
'n Foam®**

**FireBreak®**  
Flame Resistant Sealant

 **Fireblock Foam Sealant**

Touch 'n Foam® FireBreak® is an easy-to-use fire block\* foam sealant that's ideal for DIY-ers and small contractor jobs. Independent testing confirms that FireBreak resists flaming twice as long as the competition and prohibits oxygen flow into service penetrations where fire may quickly spread. Using FireBreak in these penetrations slows the fire taking it longer to move to adjoining rooms, giving one valuable time to get to safety. FireBreak is bright orange and can be easily identified as an approved fire block penetration sealant.

 **Use FireBreak to Fill**

- Space connections in soffits and drop ceilings
- Partitions and stud walls at ceilings and floors
- Top and bottom of stair stringers
- Through-penetration (electrical, plumbing, etc.)

**DIRECTIONS:** *Important – read all directions and cautions before use. Always wear gloves, eye protection and work clothes. Use drop cloths. Product is flammable during dispensing – turn off sources of ignition prior to use.*

**Preparation:** To promote adhesion, surfaces must be free of oil and dirt. Assemble straw and adapter, then carefully screw this trigger assembly onto valve. With trigger assembly attached, shake well for 30 seconds. Holding the can upside-down, slowly activate trigger until foam begins to dispense. Important: Before starting the job, first practice dispensing onto scrap materials. For best results, apply in temperatures between 60°-100°F (16°-38°C).

**Application:** This product should only be dispensed in the UPSIDE-DOWN position. For best results, apply in spaces with 40% or greater relative humidity. Fill gap no more than 1/3 full, allowing room for expansion. Do not overfill. Important: Foam will continue to dispense for a few seconds after releasing the trigger – keep the straw tip moving to reduce the possibility of overfilling. Foam is tack-free in 30 minutes and dries in 4 hours. Excess foam can be trimmed, sanded, caulked or plastered as necessary. Direct sunlight discolors foam if not painted or covered.

**Clean-up:** If wet foam contacts skin, clean immediately with acetone or nail polish remover containing acetone – do not use water. Do not attempt to remove cured foam with solvents – cured foam wears off and is not harmful to health. For more information call 1-800-325-6180 M-F, 8-5 central time, or visit our web site at [www.touch-n-foam.com](http://www.touch-n-foam.com).

**Storage/Re-Use:** To store unused portion, bend straw back onto the knob atop the dispensing trigger. To re-use, remove the straw from the knob, shake well and apply as directed. Store can upright below 90°F (32°C).



**\*NOT A FIRESTOP**  
Approved Fire block formula (ICC-ES ESR-1926)

PRODUCT #	SIZE	CASE PACK	UPC	CARTON CODE
4004501212	12 oz	12 each	0 75650 10012 7	3 00 75650 10012 8
4004510024	12 oz	24 each	0 75650 10012 7	2 00 75650 10011 4



**Convenience Products**

866 Horan Drive • Fenton, MO 63026-2416 • (800) 325-6180  
Country of origin: USA / Pays d'origine: États-Unis d'Amérique

TYPICAL PROPERTIES FireBreak	
UL94 Flammability Rating	V-0
Applicable Standards ICC-Evaluation Services (ICC-ESR-1926)	approved
Yield per can (1/2" bead)	270 linear feet
Drytime/tack free	10 minutes
Cure time	1 hour
Shelf life	12 months
ASTM C-518 R-Value	4.5/in (25 mm)
ASTM D-1621 Compressive Strength	11 psi
ASTM D-1622 Density	1.3-1.8 PCF
ASTM D-1623 Tensile Strength	26 psi
ASTM D-2856 Closed Cell Content	77%
International Building Code	compliant
International Residential Code	compliant
BOCA Building Code	compliant
1999 Standard Building Code	compliant
1997 Standard Building Code	compliant
California Bureau of Home Furnishings and Insulation	compliant



**What makes FIREBREAK the safest foam?**

- Flame resistant, all-purpose foam sealant
- Fills & seals service penetrations
- Blocks air infiltration reducing flame spread into walls and ceilings
- Orange color quickly identifies FIREBREAK for visual inspection
- Excellent performance in modified ASTM E-814 and UL-1715 tests
- Self-extinguishing formula
- UL94 Flammability Test - pass best rating V-0

**FIREBREAK self-extinguishes, while the leading brand continues to burn.**



flame removed




with flame

**vs. leading brand**



flame removed



with flame



**LISTED**

R14175 1L15

GENERAL PURPOSE CAULKING AND SEALANTS  
Listed in accordance with CAN / ULC-S102 (SURFACE BURNING)

HOMOLOGUE CALFEUTRAGE ET ENDUIT D'ÉTANCHÉITÉ CLASSIFIÉ  
Listé conformément à CAN / ULC-S102 (CHAUFFAGE DE SURFACE)

Flame Spread / Propagation de la flamme 0  
Smoke Developed / Pouvoir fumigène 5

\* Tested as applied in three 11.2 mm diameter beads, 130 mm on center (OC) covering 7.6% of the exposed test sample area.

\* Mis à l'épreuve appliqué en trois cordons de 11,2 mm de diamètre, 130 mm centre à centre recouvrant 7,6% de la zone d'échantillonnage exposée.

For more information call 1-800-325-6180,  
Monday-Friday, 8:00 a.m. - 5:00 p.m. central time.