



# Gun Foam

## Polyurethane Insulating Sealants



### ALL-PURPOSE GUN FOAM SEALANT

- Ideal sealant for all gaps & cracks
- Excellent dispensing and control
- Outperforms fiberglass / cellulose
- Class 1 foam / UL-listed
- Bright orange foam simplifies inspections
- Approved Type V residential fireblock sealant
- Meets ASTM E-814, E-84, and UL-1715



### WINDOW & DOOR GUN FOAM SEALANT

- Exerts virtually no force on frames or jambs
- Excellent dispensing and control
- Outperforms fiberglass / cellulose
- Class 1 foam / UL-listed
- Bright white / sandable - paintable
- Meets AAMA standards 812-04 for low pressure foams
- Meets ASTM E-84



### BLACK LANDSCAPING GUN FOAM SEALANT

- Excellent for ponds and waterfalls
- Great for securing landscape blocks
- Safe for plants and fish
- UV resistant - won't discolor in sunlight
- Excellent for indoor / outdoor use
- 24 oz. can yields up to 15 tubes of caulk



Always refer to local building codes prior to application of Touch 'n Foam foam sealants.

Surface to receive Touch 'n Foam foam sealants must be dry, clean and free of dust, dirt, grease and other substances that may inhibit proper adhesion.

For best results apply Touch 'n Foam Gun Foam expanding foam sealants when surface and ambient temperatures are between 60°-100°F (16°-38°C). Temperature of chemical contents must be between 50°-100°F (10°-38°C) before dispensing.

Use all chemical contents within 30 days of initial dispensing. Keep out of reach of children. Always wear proper personal protective equipment, including gloves, clothing and eyewear. Use in well-ventilated area.

Please refer to manufacturer's instructions or request a faxed set of instructions from Convenience Products by calling Customer Service at 800-325-6180.

### TECHNICAL SERVICES

Technical assistance, including more detailed information, product literature, test results, assistance with preparing project specifications and application training is available by contacting Convenience Products.



**Convenience Products**  
 866 Horan Dr., Fenton, MO 63026 USA  
 1-800-325-6180 • www.touch-n-foam.com  
 Country of Origin: USA / Hecho en E.U.A.

**TYPICAL PROPERTIES**

	ALL-PURPOSE	WINDOW & DOOR	LANDSCAPE
ASTM-814 Fireblocking (Type V)	meets	meets	—
Applicable Standards ICC-Evaluation Services (ICC-ESR-1926)	approved	approved	—
ASTM C-518 R-Value	4.5/in (25 mm)	4.5/in (25 mm)	4.5/in (25 mm)
ASTM C-1536 Yield (Linear Feet)	3200 (1/4")	1979 (1/4")	3200 (1/4")
ASTM D-1621 Compressive Strength	11 psi	11 psi	11 psi
ASTM D-1622 Density	1.3-1.8 PCF	1.3-1.8 PCF	1.3-1.8 PCF
ASTM D-1623 Tensile Strength	26 psi	26 psi	26 psi
ASTM D-2856 Closed Cell Content	77%	77%	77%
UL 1715 Fire Test (Flame/Smoke)	15/25	10/15	15/25
International Building Code	conforms	conforms	—
International Residential Code	conforms	conforms	—
BOCA National Building Code	conforms	conforms	—
1999 Standard Building Code	conforms	conforms	—
1997 Standard Building Code	conforms	conforms	—
California Bureau of Home Furnishings and Insulation	conforms	conforms	conforms
Underwriters Laboratories Classified Caulking & Sealants	conforms	conforms	conforms

**TECHNICAL DATA**

**Shelf Life**

1 year in unopened container when stored between 60°-90°F (16°-32°C), in a dry, well-ventilated area.

**Storage & Disposal**

Keep containers tightly closed in a cool, well-ventilated area. Ideal storage temperature is 60°-90°F (16°-32°C). Storage above 90°F (32°C) will reduce shelf life. Do not store at temperatures above 120°F (49°C). Do not expose containers to conditions that may damage, puncture, or burst the containers. Dispose of leftover material/containers in accordance with federal, state and local regulations. See Material Safety Data Sheet for more information.

**KEEP OUT OF REACH OF CHILDREN.**

Always wear proper personal protective equipment, including head covering, gloves, clothing, eyewear and respirator. Use in well-ventilated area.

**WARRANTY**

Convenience Products warrants its Touch 'n Foam products to be free of defects in workmanship and function. Convenience Products is not liable for any incidental, consequential or any other damages beyond the description herein, however, certain states have specific laws regarding limitation on incidental or consequential damages, in which case you may have other legal rights.

**CAN CHANGEOVER:** Once started, do not remove gun until can is empty; then purge gun and remove can. Clean gun basket with acetone or polyurethane foam cleaner. Immediately attach fresh can to prevent foam from hardening in gun.



**PREMIUM GUN**

- Metal barrel / trigger
- Durable
- Adjustable output



**ECONOMICAL GUN**

- Lightweight plastic
- Metal internal parts
- Adjustable output



**POLYURETHANE FOAM CLEANER**

- Removes uncured foam from hands, tools and gun foam applicators
- Attaches to guns to flush barrel
- Reusable dispensing

PRODUCT	PRODUCT NO.	SIZE	CASE PACK	UPC	CARTON CODE	CASE DIMENSIONS (in.)
All-Purpose Gun Foam Sealant	4006002420	24 oz.	12	0 75650 02420 1	1 00 75650 02420 8	11.25 x 8.75 x 12
Window & Door Gun Foam Sealant	4006002010	20 oz.	12	0 75650 02010 4	1 00 75650 02010 1	11.25 x 8.75 x 12
Black Landscaping Gun Foam Sealant	4006002450	24 oz.	12	0 75650 02450 8	1 00 75650 02450 5	11.25 x 8.75 x 12
Polyurethane Foam Cleaner	4006001240	12 oz.	12	0 75650 01240 6	1 00 75650 01240 3	11.50 x 8.75 x 9.25
Economical Applicator Gun	4004590604	—	6	0 75650 90604 0	1 00 75650 90604 7	7 x 13 x 15
Premium Applicator Gun	4004590609	—	1	0 75650 90609 5	—	2.25 x 6.25 x 14.50