

# Touch 'n Foam

# READY-TO-USE FOAM



## POLYURETHANE FOAM SEALANTS

• UL-LISTED • FILLS / SEALS / INSULATES • MINIMIZES ENERGY LOSS • REUSABLE • PAINTABLE / SANDABLE



### TRIPLE EXPANDING SEALANT



- 3 times the expansion to fill gaps greater than 1"
- For larger holes and gaps
- Blocks insects and other pests
- Meets ASTM E-84 Class A



### FLAME RESISTANT SEALANT



- Approved fire block penetration sealant
- Passes ASTM E-814 (modified), UL-1715, and UL-94 V-0
- Type V residential fire block
- Flame spread 5, smoke developed 0
- Easy-to-identify orange color
- Meets ASTM E-84 Class A



### MINIMUM EXPANDING SEALANT



- Fills and seals small cracks and gaps
- Water resistant



**Exclusive All-Season Formula Cures between 30°–120°F (-1°–49°C)**



### EXTERIOR FILLER-ADHESIVE



- Black foam is UV resistant
- Directs water flow in and around water gardens
- Fish and plant safe
- Superior adhesive for landscaping projects
- Fills knot holes in trees to seal out pests



### WINDOW & DOOR SEALANT



- Low pressure formula – won't bow window frames or door jambs
- Bright white foam
- Meets ASTM E-84 Class A
- Meets AAMA standards 812-04 for low pressure foams



### MULTI-PURPOSE FOAM SEALANT



- Latex-based
- Three times the adhesion strength of the leading competitor
- Performs from 35°F to 120°F
- No mess – cleans up with soap and water
- Moldable

PRODUCT	PRODUCT NO.	SIZE	CASE PACK	UPC	CARTON CODE	CASE DIMENSIONS
MaxFill	7565000043	12 oz	12	0 75650 00031 1	1 00 75650 00043 1	11.50 x 8.75 x 9.25
MaxFill	7565031612	16 oz	12	0 75650 31612 2	1 00 75650 31612 9	11.50 x 9.00 x 10.63
MaxFill	7565020012	20 oz	12	0 75650 00032 8	1 00 75650 00032 5	11.50 x 8.50 x 12.50
HomeSeal	7565000082	12 oz	12	0 75650 00082 3	1 00 75650 00082 0	11.50 x 8.75 x 9.25
No Warp	7565004000	12 oz	12	0 75650 04000 3	1 00 75650 04000 0	11.50 x 8.75 x 9.25
FireBreak	7565010012	12 oz	12	0 75650 10012 7	3 00 75650 10012 8	11.50 x 8.75 x 9.25
Landscape	7565040440	12 oz	12	0 75650 40440 9	3 00 75650 40440 0	11.50 x 8.75 x 9.25
Easy Fill	7565001208	12 oz	8	0 75650 01208 6	1 00 75650 01208 3	11.00 x 5.63 x 9.00



# READY-TO-USE FOAM

## POLYURETHANE FOAM SEALANTS

Property	Home Seal	MaxFill	No Warp	Fire Break	Landscape	Easy Fill
Shelf Life	18 months (unopened)	18 months (unopened)	18 months (unopened)	18 months (unopened)	18 months (unopened)	18 months (unopened)
Dry Time/ Tack Free Time	Less than 30 minutes	Less than 30 minutes	Less than 30 minutes	Less than 30 minutes	Less than 30 minutes	Less than 30 minutes
Fully Cured	Less than 4 hours	Less than 4 hours	Less than 4 hours	Less than 4 hours	Less than 4 hours	Less than 4 hours
Cuttability	Less than 2 hours	Less than 2 hours	Less than 2 hours	Less than 2 hours	Less than 2 hours	Less than 2 hours
ASTM E-814 (modified)	—	meets	meets	meets	meets	—
ASTM C-1536 Yield (3/8" bead - 12oz can)	357 feet	396 feet	427 feet	409 feet	410 feet	511 feet (1/4" bead)
UL 723 Surface Burning Characteristics Fire Test (ASTM E-84) (Flame/Smoke)	10/15	10/15	10/15	5/0	10/15	0/5
International Building Code	complies	complies	complies	complies	complies	complies
International Residential Code	complies	complies	complies	complies	complies	complies
Underwriters Laboratories Classified Caulking & Sealants (R14175)	listed	listed	listed	listed	listed	listed
UL 1715 (Fire Test)	—	—	—	pass	—	—

### INSTALLATION / APPLICATION

For optimal results, first practice dispensing foam onto scrap materials (HomeSeal™ must be held in upside down position). Ensure surface area is dry, clean and free of dust, dirt, grease and other substances that may inhibit adhesion. For best results, apply in temperatures between 60° and 100°F (16° and 38°C), and with 40% or greater relative humidity. Fill gap no more than 1/3 full, allowing room for expansion. When using Easy Fill®, gap can be filled up to 3/4 full. Do not overfill. Important: Foam will continue to dispense for a few seconds after releasing the trigger – keep the straw tip moving to reduce the possibility of overfilling.

### TECHNICAL DATA

#### Shelf Life

Eighteen months in unopened container when stored between 60° and 90°F, in a dry, well ventilated area.

#### Storage/Reuse

To store unused portion, bend straw back and attach to the knob atop the dispensing trigger (Note: Do not bend straw on Easy Fill product). Store can upright below 90°F (33°C). Product can be reused within three weeks if stored properly. To reuse, cut the end off the straw (removing any cured foam), shake well and apply as directed.

### KEEP OUT OF REACH OF CHILDREN.

#### First Aid

If wet foam contacts skin, do not use water to clean foam. However, water can be used to clean Easy Fill latex from skin. Do not attempt to remove cured foam with solvents – cured foam wears off and is not harmful to health.

#### Limited Warranty

If product fails to perform when used as directed, within one year from the date of purchase, call 1-888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP will not be responsible for incidental or consequential damages.

**QUESTIONS?/¿PREGUNTAS?:** Call/llame al 1-888-DAP-TIPS or visit/o visite [dap.com](http://dap.com) & click on/y pulse en “Ask the Expert.”

