



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® RapidFuse® Super Glue Adhesive with Plastic Primer Kit

### PRODUCT DESCRIPTION

DAP® RapidFuse® Super Glue Adhesive with Plastic Primer Kit sets in 30 seconds and cures in just 4 hours. Works on all common household materials, providing a durable weatherproof bond that stores well and lasts long. Get a clear bond with no dripping glue and no mess. Appropriate for indoor or outdoor use, RapidFuse® is a water-resistant super glue that bonds virtually everything.



PACKAGING	COLOR	UPC
Backer Card Tube: 0.1 oz. (3 g) Marker: 0.16 oz. (4.7 mL)	Clear	7079800171

### SUGGESTED USES

- Wood
- Aluminum
- Steel
- Rubber
- ABS
- PVC
- Melamine/Laminate HPL
- Polycarbonate
- Ceramics & Porcelain
- Glass
- Stone & Concrete
- Tile
- Leather
- Paper
- Composites
- **Polyethylene**
- **Polypropylene**
- **Polytetrafluoroethylene**



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## APPLICATION

### **INSTRUCTIONS: READ DIRECTIONS AND SAFETY INFORMATION BEFORE USE!**

**TO OPEN ADHESIVE:** Unscrew entire cap & nozzle. Remove ring. Replace cap & nozzle securely.

1. Surfaces should be dry and clean before bonding.
2. For plastics only, use primer marker to apply primer to each plastic surface and wait for 60 seconds for the primer to completely dry.
3. Unscrew adhesive cap and apply a small amount of glue to one surface.
4. Press the two surfaces together for 10 to 30 seconds.
5. Replace caps and store upright, in a cool, dry place.

**Note:**

Pretest for glass projects. Bonded items should not be placed in oven, microwave, or dishwasher.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Adhesive Base:	Ethyl Cyanoacrylate
Consistency:	Liquid
Volatile:	>2%
Non-Volatiles:	98.0%
Viscosity:	2500 cps
Flash Point:	190°F
Weight/Gallon:	9.18 lbs/gal
Odor:	Sharp
Application Temperature Range:	55°F to 85°F
Optimum Bottle Temperature:	55°F to 85°F
Service Temperature Range:	0°F to 120°F
Handling Time:	3 Minutes
Full Cure:	4 Hours
Freeze/Thaw Stability:	Stable
Coverage:	10-15ml/sq. ft.
Appearance:	Clear
Shelf Life:	18 Months Minimum @ 70°F If Unopened
Primer Base:	Heptane
Non-Volatiles:	98.0%
Flash Point:	24.8°F
Weight/Gal:	5.68 lbs/gal
Coverage:	10-15ml/sq. ft.
Appearance:	Clear
Shelf Life:	18 Months Minimum @ 70°F If Unopened

## CLEAN UP & STORAGE

Do not transfer to any other container. Keep container tightly closed. If nozzle clogs, clear with a pin.

**Prior to cure:** Clean excess adhesive with dry paper towel. After cleaning, wet any paper towel used for wiping off glue with water before disposal.

**Hands:** Soak in warm soapy water and gently peel off roll adhesive off (DO NOT PULL), flush contact area with water and seek medical attention if needed.

**After cure:** Cured adhesive must be cut or scraped away or removed with acetone. Do not use acetone or any other solvent to clean skin.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## SAFETY

**WARNING! EYE IRRITANT. BONDS SKIN INSTANTLY.** Contains ethyl cyanoacrylate. Avoid contact with skin, eyes and clothing. Avoid prolonged breathing of vapors. Use with adequate ventilation. **KEEPOUT OF THE REACH OF CHILDREN.** **FIRST AID:** Skin Contact – Soak in warm soapy water and gently peel or roll adhesive off (**DO NOT PULL**). If spilled on clothing, remove and rinse with cold water. Eye Contact – Flush with water for at least 15 minutes; contact physician. Ingestion – do not induce vomiting. If lips are bonded together, use warm water to gently separate. Contact physician. Inhalation – Remove to fresh air; contact physician.

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at [dap.com](http://dap.com) or by calling **888-DAP-TIPS**.

## WARRANTY

**WARRANTY:** DAP will provide replacement product or refund sales price if product fails to perform when used as directed within one year of the purchase date. Call 888-DAP-TIPS, with your sales receipt and product container available, to arrange for warranty fulfillment. DAP is not liable for incidental or consequential damages.

## COMPANY IDENTIFICATION

**Manufacturer:** DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224

**Usage Information:** Call 888-DAP-TIPS or visit [dap.com](http://dap.com) & click on "Ask the Expert"

**Order Information:** 800-327-3339 or [orders@dap.com](mailto:orders@dap.com)

**Fax Number:** 410-558-1068

**Also, visit the DAP website at [dap.com](http://dap.com)**